



WLH2 Firewall™ Bar Classe Series

Unparalleled dispensing and purification performance in an elegantly designed unit

Designed to provide a plentiful source of thoroughly purified ice-cold still and sparkling water, the WLH2 Firewall Bar Classe Series (WLH2 FW Bar - C Series) is a robust, reliable and sophisticated dispenser able to satisfy the water needs of environments where high volumes and high flow are in high demand.

Leading technology



High flow performance filtration

The professional grade filtration satisfies the need for dispensing high volumes of water, effectively addressing colour, taste and odour, for great tasting, quality water.



Firewall purification

High flow Firewall UVC purification thoroughly purifies the water up to the point of dispense, for micro-biologically safe water. Guaranteed free from: up to 99.9999% bacteria, 99.99% viruses and 99.9% cysts. Certified by IAPMO R&T to NSF 55 Class A and P231 standards for microbiological water purifiers.



Ice Bath cooling technology

The Ice Bath water cooling system delivers high volumes of consistent ice-cold water, catering for environments where such a need is paramount.



BioCote® antimicrobial protection

The bottle holders and floater mechanism are protected by BioCote® antimicrobial technology, proven effective against all common microbes including bacteria, mould and fungi.



*R600a gas available on 220/240v models only

Features

NSF 55 Class A and NSF P231 certified Firewall, patented UVC technology, deactivates most viruses, cysts and pathogenic bacteria, thoroughly purifying the water up to 99.9999%

Firewall UV lamp monitoring system guarantees consistent standards of water purification.

Sparkling system includes CO₂ gas pressure control and is engineered to deliver supreme quality ice-cold carbonated water, comparable to even the finest bottled water

Electronic push buttons allow for continuous dispense (max 3 litres) or pre-set portion control to fill 750 ml and 1 litre size bottles. Sequential dispense (one pre-set dispense after the other from each tap) can also be set up for peak-time usage

The ergonomic dispense area and the adjustable height drip tray are designed to accommodate various size vessels

Clearly visible dispense nozzles BioCote® protected circular bottle holders allow for accurate positioning of the bottles, preventing displacement and unnecessary water spillage

Versatile base cabinet (optional) converts the unit from countertop to freestanding, and provides additional storage space

Removable steel side plate facilitates air filter cleaning operations as dust and dirt can penetrate through the grid

LED side panel displays filter, Firewall and Ice Bath fault indicators, as well as other system diagnostics for optimum service efficiency and peace of mind

Programmable energy saving sleep mode to significantly reduce power consumption when the unit is not in use

Water options

Cold Sparkling Ambient Hot Extra hot

CS



Number of users 100+

Contact us today

Australia - www.waterlogicaustralia.com.au

1300 88 14 14

sales@waterlogic.net.au

Technical specifications

Types available

Countertop and freestanding (with base cabinet)

[Both available on request with hands-free pedal operations.]

Dimensions

Countertop (including wheels):

400 mm (W) x 607 mm (H) x 590 mm (D)

Freestanding (including cabinet):

400 mm (W) x 1392 mm (H) x 590 mm (D)

Dispense area height

22 cm-32 cm (adjustable)

Weight

Countertop: Net 48 kg

Base cabinet: Net 21.2 kg

Filtration*

High performance carbon filter

*Filter type depending on local water conditions

Storage capacity

Ice bath: 21 litres

Sparkling tank: 1 litre

Dispensing capacity

Up to 160L/h

Flow rate (P231 NSF/ANSI standard certified)

2.5-3.5 litre/min

Compressor

EU compressor (R600a): 210w ; USA compressor (R134a): 220w

Water temperature

output Cold: 3-12 °C

Sparkling: 3-12 °C

Tested and certified



The HORECA Firewall is certified by IAPMO R&T to NSF/ANSI 55 Class A, NSF P231, and US EPA Guide Standard and Protocol for Testing Microbiological Water Purifiers, and NSF 372 for lead free compliance.